

SZ-3DW

Product Size:	39x26x57cm
Oxygen flow:	0-3L/min
Power:	330W
Noise:	42dB(A)
Net weight:	16kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



SZ-5DW

J_ J	
Product Size:	39x26x57cm
Oxygen flow:	0-5L/min
Power:	500W
Noise:	45dB(A)
Net weight:	19kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function

OXYGEN CONCENTRATOR



SZ-3BW

43x31x56cm
0-3L/min
330W
48dB(A)
18.5kgs
93%±3%
With nebulizer function
0.1mL/min
oxygen density alarm function



SZ-5BW

Product Size:	43x31x56cm
Oxygen flow:	0-5L/min
Power:	500W
Noise:	52dB(A)
Net weight:	21kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



SZ-3EW

Product Size:	38x27x57cm
Oxygen flow:	0-3L/min
Power:	330W
Noise:	48dB(A)
Net weight:	16kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



SZ-5EW

J_ J	
Product Size:	38x27x57cm
Oxygen flow:	0-5L/min
Power:	500W
Noise:	52dB(A)
Net weight:	18kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function

OXYGEN CONCENTRATOR



SZ-5AW

Product Size:	47x28.5x55.6cm
Oxygen flow:	0-5L/min
Power:	500W
Noise:	52dB(A)
Net weight:	23kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function

SZ-8AW

Product Size:	47x28.5x55.6cm
Oxygen flow:	0-8L/min
Power:	650W
Noise:	55dB(A)
Net weight:	25kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



SZ-5AW-10L



Product Size:	47x28.5x55.6cm
Oxygen flow:	0-10L/min
Power:	700W
Noise:	59dB(A)
Net weight:	27kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



SZ-3AW

Product Size:	44.5x26x51cm
Oxygen flow:	0-3L/min
Oxygen new.	O OLITIMI
Power:	330W
Noise:	404D(A)
Noise:	48dB(A)
Net weight:	13kgs
O	93%±3%
Oxygen density:	93%±3%
	With nebulizer function
NI I F	0.1ml /min
Nebulizer rate:	U. IML/MIN
Optional function:	oxygen density alarm function
Optional function.	oxygen density diamin function



SS-3W

Product Size:	44.5x26x44cm
Oxygen flow:	0-3L/min
Power:	330W
Noise:	48dB(A)
Net weight:	13kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function

OXYGEN CONCENTRATOR



SS-3WB

Product Size:	42.5x24x50.5cm
Oxygen flow:	0-3L/min
Power:	330W
Noise:	48dB(A)
Net weight:	13kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



SZ-3CW

Product Size:	42.5x24x50.5cm
Oxygen flow:	0-3L/min
Power:	330W
Noise:	48dB(A)
Net weight:	13kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	0.1mL/min
Optional function:	oxygen density alarm function



Oxygen flow:	0-3L/min
Oxygen density:	93%
Battery working time:	2.4h-5h
Weight:	1.75kgs

Item No.:	SZ-1BW
Product Size:	25.5x15.5x7.5cm
Maximum flow rate:	1.2(±0.2)L/min
Air pressure:	60kPa
Power:	DC 12V
Noise:	45dB(A)
Continuous running time:	8H
Net weight:	1.5kgs
Oxygen density:	30%



OXYGEN CONCENTRATOR



SZ-1AW

Product Size:	34.5x19.5x32cm
Oxygen flow:	0-1L/min
Power:	≤150W
Noise:	≤42dB(A)
Net weight:	6kgs
Oxygen density:	93%±3%
	With nebulizer function
Nebulizer rate:	≥0.1mL/min
Optional function: oxygen density alarm function	

Oxygen Concentrator Compressor for 1L,3L,5L







PORTABLE PHLEGM SUCTION UNIT





SS-6A/SX-1A

The portable phlegm suction unit is applicable to suck thick liquid such as pus-blood and phlegm under negative pressure.

- Oil-free piston pump helps to keep from oil mist pollution.
- Plastic panel makes it resistant from water erosion.
- Overflow valve helps to prevent liquid from flowing into pump.
- . Negative pressure is adjustable according to requirements.
- Small volume and light weight, easy to carry, especially suitable for emergency and doctors going their rounds outsides.
- 1. Ultimate negative pressure value: ≥0.075MPa
- 2.Air exhausting speed: ≥15L/min (SX-1A) ≥18L/min (SS-6A)
- 3. Power supply: AC220V±22V/110V±11V, 50/60Hz±1Hz
- 4. Regulating scope of negative pressure: 0.02MPa $\,\sim\,$ maxium
- 5. Reservoir: ≥1000 mL, 1pc
- 6. Input power: 90VA
- 7. Noise: ≤65dB(A)
- 8. Suction pump: piston pump
- 9.Product Size: 28x19.6x28.5cm

PORTABLE PHLEGM SUCTION UNIT



SX-1C/SX-1E

- 1. Ultimate negative pressure value: ≥0.075MPa
- 2.Air exhausting speed: ≥15L/min (SX-1C)

≥18L/min (SX-1E)

- 3. Power supply: AC220V±22V/110V±11V, 50/60Hz±1Hz
- 4. Regulating scope of negative pressure: 0.02MPa ~ maxium
- 5. Reservoir: ≥1000 mL, 1pc
- 6. Input power: 90VA
- 7. Noise: ≤65dB(A)
- 8. Suction pump: piston pump



SX-1D

- 1. Ultimate negative pressure value: ≥0.075MPa
- 2.Air exhausting speed: ≥15L/min (SX-1D)
- 3. Power supply: AC220V±22V/110V±11V, 50/60Hz±1Hz

DC12\

- 4. Regulating scope of negative pressure: 0.02MPa ~ maxium
- 5. Reservoir: ≥1000 mL, 1pc
- 6. Input power: 65VA
- 7. Noise: ≤65dB(A)
- 8. Suction pump: piston pump
- 9.Battery working time: 30 min.

9

Electric Suction Unit



SS-8A

Electric suction unit is the new generation oil-free medical suction unit with negative pressure pump.

- Oil-free piston pump helps to keep from oil mist pollution.
- · Plastic panel makes it resistant from water erosion.
- Low noise, easy to operate with manual and pedal switches.
- · Overflow valve helps to prevent liquid from flowing into pump.
- Medical suction, high negative pressure, high flow rate.
- Negative pressure is adjustable according to requirements.

Suction pump: piston pump

Ultimate negative pressure value: ≥0.09MPa

Regulating scope of negative pressure: 0.02MPa ~ultimate

negative pressure value

Reservoir: ≥2500 mL/pc, 2pcs in the suction unit

Product Size: 36x32x43.5cm

WEIGHT SCALE

1.Body Weight:

Maximum Weight: 160kgs (352lbs)

Sub-divisions of the weight Dial: 0.5kgs

2. Height Measuring:

Height Measuring Range: 70-190cm (27 1/2 - 74 3/4 inch)

Sub-divisions of graduation: 0.5cm

3. Size of Platform (L x W): 385x280mm

4.Overall Dimensions (LxWxH): 900x350x305mm

5.Net weight: 8kgs

6.Carton size: 88*31*27cm



Air Compressing Nebulizer

Air compressing nebulizer is developed for the successful treatment of asthma, allergies and other respiratory disorders. It creates a stream of air that travels through clear air tube to the medicine cup. When air enters the medicine cup, it will convert the prescribed medication into aerosol mist for easy inhalation.

Power supply: AC 220V±22V/110V±11V, 50/60Hz, ±1Hz

Max negative pressure compressing pump: ≥0.15MPa

Free air flux compressing pump: ≥6L/min

Max nebulizing rate: ≥0.20mL/min

Noise: ≤65dB (A)







SS-7B



SS-7C



SW-1Y

Air Compressing Nebulizer

Air compressing nebulizer is developed for the successful treatment of asthma, allergies and other respiratory disorders. It creates a stream of air that travels through clear air tube to the medicine cup. When air enters the medicine cup, it will convert the prescribed medication into aerosol mist for easy inhalation.

Power supply: AC 220V±22V/110V±11V, 50/60Hz, ±1Hz

Max negative pressure compressing pump: ≥0.15MPa

Free air flux compressing pump: ≥6L/min

Max nebulizing rate: ≥0.20mL/min

Noise: ≤65dB (A)







SW-1P



SW-1M



SW-17

Other Products

First aid kit box



The health care case is made of aluminum alloy with smooth surface but without burr, flashing or rust. There are small individual cases inside the health care cases that is easier to classify different items. Size of the health care case can be designed according to the specific requirements.

Size(CM):	L *W* H	
9 inch	23 *15* 15.5cm	
11 inch	28 *15.5* 19cm	
12 inch	30.5* 16.5* 20cm	
13 inch	33* 17* 20cm	
14 inch	36* 18.5 *21cm	
16 inch	37.5* 21* 23.5cm	

Mesh Nebulizer



SW-3I

Power supply: AC 220V±22V/110V±11V.50/60Hz, ±1Hz
ADC5.0V=0.5V
Product size: 5.5'4'11.4cm
Max negative pressure compressing pump: 0.15MPa
Waterproof level: IPX1
MMDA. 4µm ± 25%
Max nebulizing rate: 0.25mL/min
Noise: 40.08 (A)

X Ray Film Viewer

X Ray film viewer is designed for observing X Ray film for medical personnel, It's applied to clinical view the medical image film.



Model	Dimension	View area	Power	Screen light uniformity	Screen light balance	Stability
Single Panel	44*50*10.5cm	36.2*42cm	30W	2000cd/m2	>70%	<2%
Double Panel	93°50°10.5cm	85°42cm	120W	2000cd/m2	>70%	<2%
Triple Panel	123*50*10.5cm	115*42cm	160W	2000cd/m2	>70%	<2%



LED X-RAY FILM VIEWER

Model	View area	Power	Screen light uniformity	Screen light balance	Stabilit y	Stand
Double Panel	70*45cm	45W / DC 12V	0~5000cd/m2	≥ 90%	<2%	bracket

Anti-decubitus mattress



Anti-decubitus mattress Lattice model

ITEM NO.: SS-001

The bubble–type alternative mattress is made of non–toxic PVC with nylon fabric. Characteristics of the alternative pump

- with nylon fabric. Characteristics of the alternative pump

 Low–noise design. The operating noise does not exceed 45dB(A)
- Safe round edge design
- Simple and lucid adjustment button
- Air pump is provided with hanger at the backside, which may save space
- Air charging pressure at the outlet of air pump is adjustable, maximum pressure ≥12kPa

Under the maximum operating load, the maximum pressure of mattress

Voltage: AC220~240V/ 100~120V 50/60hz

Max air output: ≥ 4L/min Max Pressure: ≥ 12 kPa

Cycle time:5–6min Arrangement: 2.5* bubble pad

Dimension (L*W*H): 200*90*7CM

Weight: 3.8kgs



Anti-decubitus mattress stripe Nylon material ITEM NO.: SS-002

The strip-type alternative mattress is made of non-toxic PVC with nylon fabric. There are 17 or 22 interchangeable tubes.

Characteristics of the alternative pump:

- Low-noise design. The operating noise does not exceed 45dB(A)
- Safe round edge design
- Simple and lucid adjustment button
- Air pump is provided with hanger at the backside, which may save space
- Air charging pressure at the outlet of air pump is adjustable, maximum pressure ≥ 12kPa Under the maximum operating load, the maximum pressure of mattress ≥4kPa;
- Maximum flow of air pump ≥4.5L/min;



Anti-decubitus mattress stripe PVC material ITEM NO.: SS-003

The strip-type alternative mattress is made of non-toxic PVC. There are 22 interchangeable tubes.

Characteristics of the alternative pump:

- Low-noise design. The operating noise does not exceed 45dB(A)
- Safe round edge design
- Simple and lucid adjustment button
- Air pump is provided with hanger at the backside, which may save space
- Air charging pressure at the outlet of air pump is adjustable, maximum pressure ≥ 12kPa
 Under the maximum operating load, the maximum pressure of mattress ≥ 4kPa;
- Maximum flow of air pump ≥4.5L/min;

UV Disinfection Mobile Cart







常州市凯尔德卫生材料有限公司

Address: No.73 Donghu Rd, Henglin Town, Wujin District, Changzhou, Jiangsu Province, PRC

Email: info@care-de.com

Mob:13776881257

Tel: 0086-519-83811272 /85513226

Zip: 212101



www.care-de.com